

Tapes

Sheathing Tape

Benefits of Sheathing Tapes

- High tack adhesive provides aggressive contact
- Strong and durable holding power
- Water and moisture resistant
- Excellent resistance to UV and weathering
- Prevents air infiltration
- CCMC Evaluation Report #11955-R



Applications

- Sealing of joints and seams of insulation materials
- Tape has to be pressed firmly on surface
- Should be applied on clean, dry surfaces

Technical Data

Colour	Red (02)
Backing	UV Resistant Polypropylene Film
Adhesive	Solvent Based Acrylic
Thickness3 mil
Adhesion to steel40 oz/in
Tensile strength30 lb/in
Elongation	120%
Application Temperature	-18°C (0°F) to 50°C (122°F)
Temperature Resistance	-40°C (-40°F) to 100°C (212°F)
VOC (Volatile Organic Compound) content	Estimated 0,1%
Water Vapor Transmission (ASTM E96)	0.068 perm (gr/ft ² /hr/in-Hg)
Water Penetration Rate (ASTM D3816)	0.009 g/100 in ² /24 hr
Air Permeance Rate (ASTM E2178)	0.0010 L/s m ² [0.0002 cfm/ft ²]

Sizes Available

Size	60mm x 66m -- 20 rolls/case
------	-----------------------------

Proud to be associated with



Canadian
Manufacturers &
Exporters
British Columbia Division



We are local - give us a call today!

1.866.321.1020

www.thermoflotech.com